



Product Data

Castrol Detergen® System Cleaner

Description

Castrol Detergen System Cleaner cleans contaminated lubrication systems without extra manpower - and most important of all - no production losses due to stoppage of machinery.

Detergen System Cleaner contains active ingredients - detergent as well as dispersant additives - capable of getting below solid deposits (sludge/residues).

Application

For oil circulation systems and oil reservoirs of engines, gears, compressors and hydraulic systems e.g. also when operating on conventional oils.

Add 3% to 5% volume percent of Detergen System Cleaner to the lubricant in service 40 operating hours prior to oil change. Maximum efficiency of product is at +60°C/+140°F and the maximum operating temperature is +120°C/+248°F.

Advantages

- Dissolves sludge residues into very fine particles and keeps them in suspension.
- Removes residues from hidden places cleans lubrication systems before oil changes improves the cleaning properties of low viscosity engine and hydraulic oils.
- Allows longer service life of the new oil due to clean reservoirs and lines
- Saves costs since flushing oil is not needed and cleaning is usually not required

Characteristics

	Unit	Test Method	Value
Color	-	Visual	Clear Amber
Density @ +15°C/+59°F	g/cm ³	ASTM D-1298	0.95
Viscosity @ + 40°C/+104°F	mm ² /s	ASTM D-445	227
Viscosity @+100°C/+212°F	mm ² /s	ASTM D-445	20
Flash Point	°C/°F	ASTM D -95	180/356

Subject to usual manufacturing tolerances.

Castrol Detergen System Cleaner
02.18.2008 Version Number 3.0
Detergen System Cleaner and Castrol are trademarks of Castrol limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial