



## Product Data

### Castrol Rustilo 4163

Neat corrosion preventive oil

#### Description

Castrol Rustilo™ 4163 is an oil-dispersed and fingerprint suppression corrosion preventive formulated to give long-term indoor protection. This product deposits a thin, slightly oily residual film, which is easily cleaned using an alkaline cleaner or vapour degreaser.

#### Application

Use Rustilo 4163 where:

- Operations expose the metal to water-containing machining and grinding coolants, cleaners, and water rinses.
- Parts are manually inspected or packaged
- Long-term indoor humidity protection is needed.
- Ease of cleanability is desired.

#### Advantages

- This product will provide excellent humidity protection for ferrous and nonferrous parts for up to two years in indoor storage.
- High flash point eliminates need for special fire equipment.
- Barium-free
- Excellent resistance to acid atmosphere for ferrous and nonferrous parts, which have been stored in or near acidic environments.
- Handled parts are fully protected from fingerprint corrosion because of specially formulated additives.

#### Characteristics

	Unit	Test Method	Value
Appearance	-	Visual	Clear brown fluid
Specific Gravity @ 60° F (16° C)	g/cm <sup>3</sup>	-	0.880 - 0.900
Viscosity @ 100° F (40° C)	cSt	CN-TM-101	7.0
Bulk Density	lbs/gal	-	7.5
Flash Point (COC)	°F/°C	CN-TM-039	>230°F/110°C
Film Type	-	-	Oily

Fingerprint Suppression	-	MW-TM-315	Yes
-------------------------	---	-----------	-----

## **User Advice**

### **Recommended applications and dilutions**

For best results, Rustilo 4163 should be applied by dip, flood, or spray method.

Castrol Rustilo 4163  
07/12/2005, Global Version Number 1  
Castrol, Rustilo and the Castrol logo are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563  
Tel: (877) 641 1600 Fax: (877) 648 9801

[www.castrol.com/industrial](http://www.castrol.com/industrial)